SMPRE
Precast Concrete Accessories
Strong in Manufacture of Precast Accessories

SMPRE™--Safety, Reliable and Enduring Structures!

E-MAIL: INFO@SIMENPRECAST.COM
WEBSITE: WWW.SIMENPRECAST.COM

Liffting Sockets with Plastic Caps(SLS)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
SLS12-040	12	40	2.00	0.5
SLS14-047	14	47	4.00	0.8
SLS16-055	16	55	6.00	1.2
SLS18-065	18	65	11.00	1.6
SLS20-067	20	67	13.00	2.0
SLS24-077	24	77	18.00	2.5
SLS30-105	30	105	43.00	4.0
SLS36-125	36	125	70.00	6.3
SLS42-145	42	145	106.00	8.0
SLS52-195	52	195	224.00	12.5

※Electro-galvansied and Hot-dip Galcanised is Available.
※20#,Q345B,Q345D and Stainless Steel is Available.
※Length Can Be Customized.
※Safety Factor:3.

Round Ferrule (SRF)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
SRF12-045	12	45	7.00	0.5
SRF14-050	14	50	9.00	0.8
SRF16-060	16	60	15.00	1.2
SRF18-070	18	70	26.00	1.6
SRF20-070	20	70	31.00	2.0
SRF24-080	24	80	45.00	2.5
SRF30-110	30	110	90.00	4.0
SRF36-125	36	125	150.00	6.3
SRF42-145	42	145	224.00	8.0
SRF52-195	52	195	480.00	12.5

※Electro-galvansied and Hot-dip Galcanised is Available.
※Q235,45# and Stainless Steel is Available.
※Length Can Be Customized.
※Safety Factor:3.

Elephant Foot Ferrule (SEF)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
SEF10-045	10	45	6.00	0.4
SEF12-075	12	75	12.00	0.5
SEF16-095	16	95	25.00	1.2
SEF20-095	20	95	45.00	2.0
SEF24-095	24	95	58.00	2.5
SEF30-125	30	125	117.00	4.0

※Electro-galvansied and Hot-dip Galcanised is Available.
※Q235,45# and Stainless Steel is Available.
※Length Can Be Customized.
※Safety Factor:3.

Flat Steel Socket (SFS)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
SFS12-030	12	30	4.50	0.5
SFS14-033	14	33	33.00	0.8
SFS16-035	16	35	35.00	1.2
SFS18-044	18	44	44.00	1.6
SFS20-047	20	47	47.00	2.0
SFS24-054	24	54	54.00	2.5
SFS30-072	30	72	72.00	4.0
SFS36-084	36	84	84.00	6.3
SFS42-098	42	98	98.00	8.0
SFS52-117	52	117	117.00	12.5

※Electro-galvansied and Hot-dip Galcanised is Available.
※20#,Q345B,Q345D and Stainless Steel is Available.
※Length Can Be Customized.
※Safety Factor:3.

Crown Foot Anchor (SCFA)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
SCFA12-060	12	60	8.00	0.5
SCFA14-070	14	70	10.00	0.8
SCFA16-080	16	80	15.00	1.2
SCFA20-100	20	100	34.00	2.0
SCFA24-115	24	115	54.00	2.5
SCFA30-120	30	120	88.00	4.0

※Electro-galvansied and Hot-dip Galcanised is Available.
※Q235,45# and Stainless Steel is Available.
※Length Can Be Customized.
※Safety Factor:3.

Straight Threaded Anchor (STA)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
STA12-195	12	195	9.00	0.5
STA14-235	14	235	17.00	0.8
STA16-275	16	275	28.00	1.2
STA18-305	18	305	43.00	1.6
STA20-355	20	355	64.00	2.0
STA24-405	24	405	76.00	2.5
STA30-505	30	505	156.00	4.0
STA36-570	36	570	310.00	6.3
STA42-620	42	620	467.00	8.0

※Electro-galvansied and Hot-dip Galcanised is Available.
※Length Can Be Customized.
※Safety Factor:3.

Threaded Anchor System

Short Wavy Tail Threaded Anchor (STAS)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
STAS12-110	12	110	6.00	0.5
STAS14-130	14	130	11.00	0.8
STAS16-170	16	170	20.00	1.2
STAS18-175	18	175	27.00	1.6
STAS20-187	20	187	37.00	2.0
STAS24-240	24	240	50.00	2.5
STAS30-300	30	300	105.00	4.0
STAS36-380	36	380	186.00	6.3
STAS42-450	42	450	285.00	8.0

※Electro-galvansied and Hot-dip Galcanised is Available.
※Length Can Be Customized.
※Safety Factor:3.

Long Wavy Tail Threaded Anchor (STAL)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
STAL12-137	12	137	7.00	0.5
STAL14-170	14	170	14.00	0.8
STAL16-216	16	216	24.00	1.2
STAL18-235	18	235	35.00	1.6
STAL20-257	20	257	49.00	2.0
STAL24-350	24	350	67.00	2.5
STAL30-450	30	450	139.00	4.0
STAL36-570	36	570	260.00	6.3
STAL42-620	42	620	365.00	8.0

※Electro-galvansied and Hot-dip Galcanised is Available.
※Length Can Be Customized.
※Safety Factor:3.

Compact Anchor(SCA)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
SCA12-100	12	100	6.00	0.5
SCA14-155	14	155	13.00	0.8
SCA16-175	16	175	17.00	1.2
SCA18-225	18	225	36.00	1.6
SCA20-250	20	250	43.00	2.0
SCA24-275	24	275	52.00	2.5
SCA30-350	30	350	126.00	4.0
SCA36-450	36	450	227.00	6.3
SCA42-500	42	500	323.00	8.0

※Electro-galvansied and Hot-dip Galcanised is Available.
※Length Can Be Customized.
※Safety Factor:3.

Lifting Loop (SLL)

Ref.- No.	Type M/RD	Length MM	Weight Kg/100Pcs	W.L.L T
SLL-12	12	155	6.00	0.5
SLL-14	14	155	9.50	0.8
SLL-16	16	165	13.00	1.2
SLL-18	18	190	19.00	1.6
SLL-20	20	215	26.00	2.0
SLL-24	24	255	46.00	2.5
SLL-30	30	300	88.00	4.0
SLL-36	36	360	145.00	6.3
SLL-42	42	425	216.00	8.0
SLL-52	52	530	450.00	12.5

※7*19,1770Mpa High Strength Wire Rope.
※Length According to Requirement.
※Safety Factor:4.

Plastic Plug (SPP)

Ref.- No.	Type M/RD	Weight Kg/100Pcs
SPP-12	12	0.4
SPP-14	14	0.4
SPP-16	16	0.4
SPP-18	18	0.4
SPP-20	20	0.4
SPP-24	24	0.5
SPP-30	30	0.5
SPP-36	36	0.5
SPP-42	42	0.6
SPP-52	52	0.6

Magnetic Plug (SMP)

Ref.- No.	Type M/RD	Weight Kg/100Pcs
SMP-10	10	7.00
SMP-12	12	8.00
SMP-14	14	14.00
SMP-16	16	15.00
SMP-18	18	19.00
SMP-20	20	20.00
SMP-24	24	22.00
SMP-30	30	32.00
SMP-36	36	36.00
SMP-42	42	48.00
SMP-52	52	50.00